



The Right Connection™

OSHA Compliant Products

Dixon OSHA compliant products will help you meet several OSHA requirements concerning the use of hose couplings and related accessories.

These products are available from our large distributor base throughout the U.S. Please see the current DPL (Dixon Price List) or visit us online at dixonvalve.com for complete product descriptions and more information on the rest of Dixon's product line.

OSHA regulations may be viewed in full on the OSHA website osha.gov.

OSHA Standard	Dixon Product	Product Description
1926.302(b2)	Air King safety clip	for securing Air King Universal couplers
1910.169	ASME air receiver manifolds	7 gallon tank with Air King couplers 7 gallon tank with Watts Filter 7 gallon tank frame
1910.147	bronze ball valve with NPT tap for drain	Vents downstream air; has NPT tap for noise muffler or venting elbow.
1910.95	conical muffler	reduces noise levels below 90 dBA
1910.242(b)	extended nozzle pistol grip	tip pressure will not exceed 30 PSI
1910.95	safety blowgun	reduces noise levels below 90 dBA
1910.95	muffler/filter	reduces noise levels below 90 dBA
1910.242(b) 1910.95	pistol grip safety blowgun and premium safety blowgun	tip pressure will not exceed 30 PSI reduces noise levels below 90 dBA
1910.242(b)	push button controlled pressure safety blowgun	tip pressure will not exceed 30 PSI
1910.242(b) 1910.95	safety blowgun and safety air booster blowgun	tip pressure will not exceed 30 PSI reduces noise levels below 90 dBA
1926.302(b7)	safety check valve	Prevents hose whip during accidental fitting separation or pressure surge.
1910.147	safety vented ball valve	vents downstream air
1926.302(b1)	King safety cable	Prevents hose whip during accidental separation of hose assembly.

Dixon

800 High Street • Chestertown, Maryland 21620
Customer Service: 877-963-4966 • Fax: 800-283-4966
dixonvalve.com